

WIR SYS 7518

MID-RANGE INFRARED SYSTEM



[BEAUTY PAIRED WITH UNPARALLELED COVERAGE]

NEW This system features the NEW WIR TX75 infrared transmitter, ensuring participants in a conference room, courtroom, classroom or other mid-sized venue receive direct, clear communication of your message without sacrificing security. Includes comfortable, stethoscope-style, WIR RX18 infrared receivers—ideal for single- or two-channel applications. The sleek and stylish TX75 is designed to maximize coverage area up to 4,000 square feet

(transmitter with WIR TX75-S slave) in single-channel mode. One additional slave (sold separately) can be added for additional coverage of up to 2,000 square feet each (for total coverage of up to 6,000 square feet). Placing additional slaves in the same room increases coverage and enhances freedom of movement. A single CAT-5 cable carries both power and signal to slaves—truly a one-cable connection. Mounting brackets and power supply are included.

WIR SYS 7518

MID-RANGE INFRARED SYSTEM



SYSTEM INCLUDES

- (1) WIR TX75 infrared transmitter
- (1) WIR TX75-S slave emitter
- (5) WIR RX18 stethoset-style, infrared receivers
- (1) CHG 518 five-bay, drop-in charger
- (1) BKT 024 wall / ceiling mounting bracket
- (1) MLB 003 slave linking bar
- (1) TFP 046 international power supply with WLC 004 U.S. mains AC plug
- (1) IDP 008 ADA wall plaque

APPLICATIONS

- Courtrooms
- Conferences
- Houses of Worship
- Universities
- Cinema

FEATURES/BENEFITS

- Looks great! Sleek, professional styling complements room aesthetics.
- Additional TX75-S slave emitter is available for use with the WIR SYS 7518 (sold separately).
- Front cover can be painted to match décor
- Headset and body-pack receivers also available for use with WIR SYS 7518 (sold separately).
- Robust digital communication bus between master and slave unit reduces interference.
- Master unit has troubleshooting lights built in to simplify installation.
- Separate RCA audio inputs for each channel (2.3/2.8 MHz on the TX75, 3.3/3.8 MHz on the TX75b) accept balanced or unbalanced line level inputs; use together for stereo operation or separately for mono.
- Unit senses if only one channel is in use and doubles the output power on that channel for twice the coverage.
- Green power—if no audio is present after a few minutes, unit automatically disables power to IR diodes, reducing power consumption by 80 percent.